

ROLLER DOOR AQUISO BLUE

FIRE-RETARDANT | TIGHT-CLOSING / SMOKE-TIGHT

ROLLER DOOR AQUISO BLUE

WINNER

of the GERMAN

FIRE SAFETY AWARD

DOOR CURTAIN

The door curtain consists of high-grade aluminium hollow sections measuring 114 mm in height. The individual slats are joined using a hinged connect-ing system. The elements are 33 mm thick. The gate has safety equipment, including an-ti-fall-back device in accordance with DIN 12604.

GUIDE RAIL

The guide rail is 112 mm wide and made of galvanised sheet steel in a bolted design.

RAISED INSTALLATION

Jansen is able to offer roller doors for use as counter shutters with a fire rating of El₂ 30 C2 S₂₀₀.

OPTION

Available as a counter shutter with raised installation.

A specially matched drive and control system (microprocessor-controlled hold-open system) that has been approved by the building inspectorate is used.

Use as a functional gate possible. Thanks to various freely adjustable parameters in the control sys-tem, the AQUISO blue roller door can be operated like a standard industrial installation (e.g. traffic lights, timed closure, etc., see op-tional features).

A battery backup means that the door will be held in its current position if there is a power cut. The fire control system and all safety devices remain active.

box no

Extras:
Flaps for tion, bar protects and system system.

The door's operating status can be interrogated by means of floating contacts. It is possible to connect an on-site fire alarm using existing interfaces.

OPTIONAL FEATURES

- Surface coating: Primer, RAL, DB or NCS colours
- Electrical options: Pulse control system, timed closure
- Controls: Smoke detector, key-operated push button, release button
- Box:
 To hide the shaft and rolled-up curtain, for visual purposes, box not required for approval
- Extras:
 Flaps for invisible fire protection, barrel casing / box, chain protection, special control system for AGV

Scan for relevant dimensions











