

ROLLER GATES AQUISO BLUE

FIRE-RETARDANT | TIGHT-CLOSING / SMOKE-TIGHT

ROLLER GATE AQUISO BLUE

WINNER
of the GERMAN
FIRE SAFETY AWARD

GATE CURTAIN

The gate curtain consists of high-grade aluminium hollow sections measuring 114 mm in height. The individual slats are joined using a hinged connecting system. The elements are 33 mm thick. The gate has safety equipment, including anti-fall-back device in accordance with DIN 12604.

GUIDE RAIL

The guide rail is 112 mm wide and made of galvanised sheet steel in a bolted design.

RAISED INSTALLATION

Jansen is able to offer roller gates for use as counter shutters with a fire rating of El₂ 30 C2 S_a / El₂ 30 C2 S₂₀₀.

OPTION

Available as a counter shutter with raised installation.

A specially matched drive and control system (microprocessor-controlled hold-open system) that has been approved by the building inspectorate is used.

Use as a functional gate possible. Thanks to various freely adjustable parameters in the control system, the AQUISO blue roller gate can be operated like a standard industrial installation (e.g. traffic lights, timed closure, etc., see optional features).

A battery backup means that the gate will be held in its current position if there is a power cut. The fire control system and all safety devices remain active.

The gate's operating status can be interrogated by means of floating contacts.

It is possible to connect an on-site fire alarm using existing interfaces.

OPTIONAL FEATURES

- Surface coating: Primer, RAL, DB or NCS colours
- Electrical options: Pulse control system, timed closure
- Controls: Smoke detector, key-operated push button, release button
- Box:
 To hide the shaft and rolled-up curtain, for visual purposes,
 box not required for approval
 - Extras:
 Flaps for invisible fire protection, barrel casing / box, chain protection, special control system for AGV

Scan for relevant dimensions











